

OTB-007 1U BOX Specifications



Product description:

Slidable Rack-mount Fiber Optic Distribution BOX has aluminum sliding fittings with self-locking functions prevent the drawer from falling when moved; 19-inch rack mount for ST, SC, LC, E2000, FC adapters. The drawer is the holding board for splicing, easy to withdraw the fibers when testing and distributing. The wiring box is made of cold rolled materials, and the paint surface adopts electrostatic spraying method.

Features:

- ❖ Standard size, light weight and reasonable structure.
- ❖ Slide out drawer for easy cable management.
- ❖ Suitable for ribbon and single fiber.
- ❖ Compact design for space saving.
- ❖ Various panel plate to fit different adapter interface.
- ❖ Front mark on the plate is easy for identification and operation.
- ❖ Easy for management and operation.

Application:

- ★. Telecommunications subscriber loop
- ★. Fiber to the home (FTTH)
- ★. LAN/WAN
- ★. CATV

Mechanical and environmental characteristics:

Projects	Parameter
Operating temperature	-25℃~+40℃
Storage temperature	-25℃~+55℃
Relative humidity	≤85%(+30℃)
Air pressure	70Kpa~106Kpa
Color	Beige or Black

Specifications and Models:

Model	Fiber Quantity		Height	Dimension(LxWxH)	Weight(Kg)
	FC,SC,ST,E2000	LC			
OTB-007-24C	24	48	1U	435mmx300mmx44.5mm	5.0

Outline drawing:

